

SLOAN AG
Birmannsgasse 8
CH-4009 Basel
Switzerland
Tel.: +41 (0) 61 264 10 60
Fax: +41 (0) 61 264 10 75
E-Mail: sloan@sloan-basel.com
www.sloan-basel.com



ATTENTION

Observe Precautions
for Handling
Electrostatic Sensitive
Devices

12V Blue-LED-Flashing-Unit (replacing conventional blue flashing-lights)



Electrical Characteristics

- Supply Voltage: 10 – 18.5VDC
- Polarity protected
- Up to 4 LED-Clusters per Drive-unit

Applications

- Police-vehicles
- Military-/ Special-Forces-vehicles
- VIP- & Diplomatic-vehicles
- Fire-engines
- Ambulances/Paramedic-vehicles

Features

- Highbright, real-blue 470 nm
- Easy and fast installation on dashboard or behind grilleguard
- High reliable lightsource, no heat dissipation
- Long lifetime
- Low power consumption
- 12V low voltage operation, no high voltage generator required
- LED-Clusters and Drive-unit in small size, minimum space required

Optical Characteristics

- Brightness: 101 – 126cd per cluster
- Frequency: 2Hz
- Approved and certified in Switzerland

Environment

- Temperature: -25°C ~ +55°C
- Waterproof: IP64 (LED-Cluster)